

Wikiprint Book

Title: Trac Permissions

Subject: Ecopath Developer Site - TracPermissions

Version: 2

Date: 2024-04-17 13:47:44

Table of Contents

Trac Permissions	3
Graphical Admin Tab	3
Available Privileges	3
Repository Browser	3
Ticket System	3
Roadmap	4
Reports	4
Wiki System	4
Permissions	4
Others	4
Granting Privileges	4
Permission Groups	5
Adding a New Group and Permissions	5
Removing Permissions	5
Default Permissions	6

Trac Permissions

Trac uses a simple, case sensitive, permission system to control what users can and can't access.

Permission privileges are managed using the [trac-admin](#) tool or (new in version 0.11) the *General / Permissions* panel in the *Admin* tab of the web interface.

In addition to the default permission policy described in this page, it is possible to activate additional permission policies by enabling plugins and listing them in the [trac] `permission_policies` configuration entry in the [TracIni](#). See [TracFineGrainedPermissions](#) for more details.

Non-authenticated users accessing the system are assigned the name "anonymous". Assign permissions to the "anonymous" user to set privileges for anonymous/guest users. The parts of Trac that a user does not have the privileges for will not be displayed in the navigation. In addition to these privileges, users can be granted additional individual rights in effect when authenticated and logged into the system. All logged in users belong to the virtual group "authenticated", which inherits permissions from "anonymous".

Graphical Admin Tab

This feature is new in version 0.11.

To access this tab, a user must have `TRAC_ADMIN` privileges. This can be performed as follows (more on the `trac-admin` script below):

```
$ trac-admin /path/to/projenv permission add bob TRAC_ADMIN
```

Then, the user bob will be able to see the Admin tab, and can then access the permissions menu. This menu will allow you to perform all the following actions, but from the browser without requiring root access to the server (just the correct permissions for your user account).

An easy way to quickly secure a new Trac install is to run the above command on the anonymous user, install the [?AccountManagerPlugin](#), create a new admin account graphically and then remove the `TRAC_ADMIN` permission from the anonymous user.

Available Privileges

To enable all privileges for a user, use the `TRAC_ADMIN` permission. Having `TRAC_ADMIN` is like being root on a *NIX system: it will allow you to perform any operation.

Otherwise, individual privileges can be assigned to users for the various different functional areas of Trac (**note that the privilege names are case-sensitive**):

Repository Browser

BROWSER_VIEW	View directory listings in the repository browser
LOG_VIEW	View revision logs of files and directories in the repository browser
FILE_VIEW	View files in the repository browser
CHANGESET_VIEW	View repository check-ins

Ticket System

TICKET_VIEW	View existing tickets and perform ticket queries
TICKET_CREATE	Create new tickets
TICKET_APPEND	Add comments or attachments to tickets
TICKET_CHGPROP	Modify ticket properties (priority, assignment, keywords, etc.) with the following exceptions: edit description field, add/remove other users from cc field when logged in, and set email to pref
TICKET_MODIFY	Includes both <code>TICKET_APPEND</code> and <code>TICKET_CHGPROP</code> , and in addition allows resolving tickets . Tickets can be assigned to users through a drop-down list when the list of possible owners has been restricted.
TICKET_EDIT_CC	Full modify cc field
TICKET_EDIT_DESCRIPTION	Modify description field
TICKET_EDIT_COMMENT	Modify comments
TICKET_ADMIN	All <code>TICKET_*</code> permissions, plus the deletion of ticket attachments and modification of the reporter and description fields. It also allows managing ticket properties in the WebAdmin? panel.

Attention: the "view tickets" button appears with the REPORT_VIEW permission.

Roadmap

MILESTONE_VIEW	View milestones and assign tickets to milestones.
MILESTONE_CREATE	Create a new milestone
MILESTONE_MODIFY	Modify existing milestones
MILESTONE_DELETE	Delete milestones
MILESTONE_ADMIN	All MILESTONE_* permissions
ROADMAP_VIEW	View the roadmap page, is not (yet) the same as MILESTONE_VIEW, see ?#4292
ROADMAP_ADMIN	to be removed with ?#3022 , replaced by MILESTONE_ADMIN

Reports

REPORT_VIEW	View reports , i.e. the "view tickets" link.
REPORT_SQL_VIEW	View the underlying SQL query of a report
REPORT_CREATE	Create new reports
REPORT_MODIFY	Modify existing reports
REPORT_DELETE	Delete reports
REPORT_ADMIN	All REPORT_* permissions

Wiki System

WIKI_VIEW	View existing wiki pages
WIKI_CREATE	Create new wiki pages
WIKI_MODIFY	Change wiki pages
WIKI_RENAME	Rename wiki pages
WIKI_DELETE	Delete wiki pages and attachments
WIKI_ADMIN	All WIKI_* permissions, plus the management of <i>readonly</i> pages.

Permissions

PERMISSION_GRANT	add/grant a permission
PERMISSION_REVOKE	remove/revoke a permission
PERMISSION_ADMIN	All PERMISSION_* permissions

Others

TIMELINE_VIEW	View the timeline page
SEARCH_VIEW	View and execute search queries
CONFIG_VIEW	Enables additional pages on <i>About Trac</i> that show the current configuration or the list of installed plugins
EMAIL_VIEW	Shows email addresses even if ?trac show_email_addresses configuration option is false

Granting Privileges

You grant privileges to users using [trac-admin](#). The current set of privileges can be listed with the following command:

```
$ trac-admin /path/to/projenv permission list
```

This command will allow the user *bob* to delete reports:

```
$ trac-admin /path/to/projenv permission add bob REPORT_DELETE
```

The permission add command also accepts multiple privilege names:

```
$ trac-admin /path/to/projenv permission add bob REPORT_DELETE WIKI_CREATE
```

Or add all privileges:

```
$ trac-admin /path/to/projenv permission add bob TRAC_ADMIN
```

Permission Groups

There are two built-in groups, "authenticated" and "anonymous". Any user who has not logged in is automatically in the "anonymous" group. Any user who has logged in is also in the "authenticated" group. The "authenticated" group inherits permissions from the "anonymous" group. For example, if the "anonymous" group has permission WIKI_MODIFY, it is not necessary to add the WIKI_MODIFY permission to the "authenticated" group as well.

Custom groups may be defined that inherit permissions from the two built-in groups.

Permissions can be grouped together to form roles such as *developer*, *admin*, etc.

```
$ trac-admin /path/to/projenv permission add developer WIKI_ADMIN
$ trac-admin /path/to/projenv permission add developer REPORT_ADMIN
$ trac-admin /path/to/projenv permission add developer TICKET_MODIFY
$ trac-admin /path/to/projenv permission add bob developer
$ trac-admin /path/to/projenv permission add john developer
```

Group membership can be checked by doing a permission list with no further arguments; the resulting output will include group memberships. **Use at least one lowercase character in group names, as all-uppercase names are reserved for permissions.**

Adding a New Group and Permissions

Permission groups can be created by assigning a user to a group you wish to create, then assign permissions to that group.

The following will add *bob* to the new group called *beta_testers* and then will assign WIKI_ADMIN permissions to that group. (Thus, *bob* will inherit the WIKI_ADMIN permission)

```
$ trac-admin /path/to/projenv permission add bob beta_testers
$ trac-admin /path/to/projenv permission add beta_testers WIKI_ADMIN
```

Removing Permissions

Permissions can be removed using the 'remove' command. For example:

This command will prevent the user *bob* from deleting reports:

```
$ trac-admin /path/to/projenv permission remove bob REPORT_DELETE
```

Just like permission add, this command accepts multiple privilege names.

You can also remove all privileges for a specific user:

```
$ trac-admin /path/to/projenv permission remove bob '*'
```

Or one privilege for all users:

```
$ trac-admin /path/to/projenv permission remove '*' REPORT_ADMIN
```

Default Permissions

By default on a new Trac installation, the anonymous user will have *view* access to everything in Trac, but will not be able to create or modify anything. On the other hand, the authenticated users will have the permissions to *create and modify tickets and wiki pages*.

anonymous

```
BROWSER_VIEW  
CHANGESET_VIEW  
FILE_VIEW  
LOG_VIEW  
MILESTONE_VIEW  
REPORT_SQL_VIEW  
REPORT_VIEW  
ROADMAP_VIEW  
SEARCH_VIEW  
TICKET_VIEW  
TIMELINE_VIEW  
WIKI_VIEW
```

authenticated

```
TICKET_CREATE  
TICKET_MODIFY  
WIKI_CREATE  
WIKI_MODIFY
```

See also: [TracAdmin](#), [TracGuide](#) and [TracFineGrainedPermissions](#)